
Economy & Infrastructure Dashboard - Overview & Scrutiny




Percentage of inspections meeting national guidelines in Code of Practice for Maintenance Management "Well Maintained Highways".



The average time it takes for standard Traffic Regulation Orders from initiation to implementation, not including those in association with Development Control planning issues and Internal Generated Schemes. This can be a consultation process that involves external bodies such as West Mercia Police and District Councils. Whilst there are agreed timescales for their responses, they do not always meet these. The process can also involve Legal Services when there are formal objections which can delay the process. Additionally, construction issues can cause considerable delays.




The number of Highways Development Control planning applications received each month and the percentage responded to within the required 21 days. This relates only to us providing our recommendation to the planning authority on the application and is not linked to Highways Act section 278 and section 38 agreements.



This graph shows the percentage of footways and roads (Principal, Non-Principal and Unclassified) considered for maintenance after completion of the annual Coarse Visual Inspection (CVI) survey of the network. This is carried out from a slow-moving vehicle. A large part of a highways authority's road network is assessed each year. To produce the report, two years' data is combined, half the data being carried over from the previous year. Each year, 50% of Unclassified roads are the subject of a CVI. This exceeds the Department for Transport requirement of 25% inspection-coverage per annum. 'Major maintenance' is repairs to the edging, surface or structure of the carriageway. These involve at least one of edge patching or strengthening, carriageway strengthening (overlay, partial re-construction or full depth re-construction) or carriageway re-surfacing (inlay or overlay). Technical indices for edging, surface, and structure condition determine the point at which works are deemed necessary.




The percentage of instructed highway defects that have been completed on time. For a pothole to be defined and fixed, it is usually deeper than 20mm and wider in diameter than 200mm for a footway and deeper than 40mm and wider in diameter than 200mm for a carriageway.




The percentage of principal (A roads) and non-principle roads (B & C roads) that are deemed to require major maintenance following the annual Surface Condition Assessment of the National NEtwork of Roads (SCANNER) survey.



The percentage of PEMs (customer enquiries) completed on time within the last month period, in accordance with the 28-day Service Level Agreement.



The number of Highways PEMs outstanding as at the last day of the month. The oldest open/outstanding PEM in the system was recorded on 16th November 2015.



The columns show the total energy used for lighting County Council-owned street lights, whilst the lines indicate the amount spent on streetlighting per month.

